

Cut-N-Seal[®]

WOOD PRESERVATIVE

for cuts, holes, and injuries in
pressure treated wood above ground

Technical Data Sheet

Product Description

Cut-N-Seal[®] is a brush-on wood preservative for saw cuts and holes in pressure treated wood that expose untreated wood above ground where appearance counts, on deck boards, railing, post tops and fence boards.

Cut-N-Seal is a ready-to-use, copper-based, waterborne formula that is low VOC and low odour. It is available in a Sienna/Cedar colour that is colour-matched to MicroPro Sienna[®] Treated Wood.

Uses

For pressure treated wood **above ground**, Cut-N-Seal is used to protect the areas of exposed untreated wood caused from saw cuts and drill holes on deck boards, post tops and fence boards. Cut-N-Seal is not to be used in ground contact applications, in preserved wood foundations, to recoat pressure treated wood surfaces or as a replacement for pressure treatment. For exterior use only.

Properties*

Contains copper(II) carbonate hydroxide and n-Alkyl dimethyl benzyl ammonium chloride.

Physical State: Suspension, aqueous-based

Freezing Point: 0°C (32°F)

Stability of Freeze/Thaw Cycle: Avoid freezing.
Keep above 4°C (40°F)

pH: 8.0-9.0

Density: 1.03 g/cm³

Appearance and Odour: No specific odour.
Liquid suspension. Colour may vary.

* Data generated directly from product sample.

Packaging

946 ml plastic can / 6 or 10 per tray
3.78 L plastic jug / 4 per tray

Application

- Pressure treated wood should be clean and dry.
- Cut-N-Seal is ready-to-use – do not dilute.
- Shake and stir contents before and periodically during use.
- Apply a first coat by brush, allow to absorb, and apply a second coat. Do not spray or dip.
- Apply at a temperature above 10°C (50°F)
- Clean up with soap and water.
- Dispose of empty container in household trash.

Detailed instructions are given on the product label. Follow the manufacturer's recommendations on the product label.

Coverage

A 946 ml can will seal with two coats approx. 330 5/4x6 deck board ends or approx. 220 2x6 deck board ends.

Storage

Store in tightly closed container. **Keep from freezing.**
Keep above 4°C (40°F).

Safety Measures

Avoid contact with the eyes and skin; wear eye protection and rubber gloves. Keep out of the reach of children. Refer to the product label on the container and safety data sheet for further information.



35 Crawford Crescent, P.O. Box 520
Campbellville ON L0P 1B0
Tel: (905) 854-2244
Fax: (905) 854-0834